



VLXS SERIES LOW RISE PAD LIFTS

7,000 - 10,000 lbs. / QUICK SERVICE LIFTS

VLXS10/VLXS7 FIXED PAD / QUICK SERVICE LIFTS

Increasing Productivity with Rotary Lift

The VLXS low-rise lift is your solution for quick service operation on today's passenger cars and trucks up to 10,000 lbs. Tire and brake work can now be performed on a wider variety of vehicles, thanks to the lift's pads, adapters, wider drive-over capability. The vehicle spotting combinations allow lifting of uni-body and frame engagement — reaching recommended manufacturers pick-up points on most vehicles on the road today.

FEATURES:

MODEL SHOWN: VLXS10000BL

- 10,000 and 7,000 lbs. capacity models
- Dual lifting cylinders
- Non-slip deck padding provides surface for adapters or vehicle pick-up points
- Ramps and side drive-over areas accomodate wider wheelbases
- ALI Gold Certified

Rotary Lift



VLXS10 3-Position Adapters Rubber contact pads on three sides increase the positioning capabilities.



The VLXS10 also comes with a set of four 1 1/2" rubber block adapters for low-profile vehicles.

VLXS7 Rubber Block Adapters

Standard with a set of four (4) each rubber blocks for quick access to lower profile and unibody frame vehicles. Blocks are 11/2" and 3" in height.

Sales: 800.445.5438

insidesales@vsgdover.com

Tech. Support: 800.445.5438

technicalsupport@rotarylift.com



VLXS7/10 PAD LIFTS

MODEL SHOWN:

VLXS7000BL

Ent colors are blue and ned	PAD LIFTS
SURFACE MOUNT	VLXS7000 VLXS10000
Lift Capacity	7,000 lbs. 10,000 lbs.
Rise*	21 3/4" Flat Rise 23 1/4" Short Pad 26 1/4" Low Step 28 1/16" Mid Step 30 5/16" High Step / Tall Pad
Width Overall	78 1/2"
Width Between Platforms	22 3/4"
Length Overall	90 1/2"
Length of Platform	51 1/4"
Length of Pad	17"
Outside Width of Platforms	70 3/4"
Lowered Height	4"
Horizontal Movement	16" During Rise
Locking Leg Heights	13 3/8" / 17 3/8" / 21 3/8"
Single Voltage Phase	115v
Time of Full Rise	40 seconds
*Rise measures floor to top of supplied adapters at full stroke	

*Rise measures floor to top of supplied adapters at full stroke. Surface mounted measurement.

Global Contact Information USA: 1.812.273.1622 Canada: 1.905.812.9920 Latin America / Caribbean: 1.812.273.1622 Brazil: +55.11.4534.1995

Government Sales: 800.445.5438 X5655

North / South America Information

For additional information: rotarylift.com/Government-Purchasing-Assistance/

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability



Lit# Rotary VLXS SERIES Cutsheet.2021.11

(2021) VEHICLE SERVICE GROUP^{EA}, Printed in U.S.A., All Rights Reserved, Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP^{EA}, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

2700 Lanier Drive / Madison, IN 47250, USA

rotarylift.com 🛐 🞯 🔽 💽 🔃