

# R1200 LEVERLESS PRO

PREMIUM CENTER LOCKING CHANGER WITH VARIABLE SPEED CONTROL

## AUTOMATIC LEVERLESS TIRE CHANGER WITH SYNCHRONIZED DUAL BEAD BREAKING ROLLERS

### HUB MOUNTED, DUAL ROLLER SYSTEM REQUIRES NO TOOLS

There's no metal-to-metal contact with patented leverless mount / demount tool. The bead breaker system and tool simultaneously position in one simple movement. Demount and mount the most challenging tire and wheel combinations - normal and reverse rims, run flat, and SST.

### 0-15 RPM VARIABLE SPEED TURNTABLE MOTOR

Exclusive inverter regulates rotational speed and slows as the stress on the bead increases, avoiding any damage to the tire.

### STANDARD with THE R1200

- Integrated pneumatic wheel lift
- 3-position pedestal with self-locking plate - handle wheels with a 10" to 30" diameter
- Quick-lock rim clamping device with guard
- Centering adapter / double conic
- Rubber turntable guard
- Pin protectors for centering pulling unit
- Bead pusher to assist seating bead to rim
- Foot pedal controls for inflation, rotation and wheel lift
- Inflation station
- Storage cabinet
- Tire paste lubricant and brush



### EASY CONTROLS

Easy to use two-button controls are operated from a single location.



### AUTO INDENT

Up / down positioning of dual rollers and tool head height.



### TIRE DEMOUNTING

- The tool enters between bead and rim
- Levering on the rim, the tool pulls up the bead, minimizing tire stress

**DUAL BEAD-BREAKING ROLLERS**  
Accurate and easy positioning and operation of both rollers and mount / demount tool.

**EASY TIRE MOUNTING**  
with plastic tool, dual rollers top bead helper arm and power-assisted to bead press arm.



### PATENTED POWERFUL TOP INFLATION

Safe tubeless bead blast tire inflation system works on any rim diameter.



Features pedal-operated inflation with gauge and pressure-reduced quick inflating valve.

### R1200 LEVERLESS PRO services:



Optional equipment may be required

### OPTIONAL ACCESSORIES

#### VSG1000A158

Universal flange for reverse, and Chrome Clad wheels

#### VSG1000A152

Light truck adapter for centering locking tire changer - 19.5" wheels

#### VSG1000A102

5 stud kit 110mm long for reverse rims. Used on VSG1000A87

#### VSG1000A86

Re-positionable side mirror



Lit# Rotary R1200 Changer Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability. ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.

Site Requirements:  
220V / 1Ø / 20 amp power supply / 115-145 psi air supply



SCAN CODE FOR PRODUCT VIDEO

TECHNICAL DATA	R1200
Clamping range	10" - 30"
Maximum tire width	19**
Maximum tire diameter	45"
Bead breaker power (each arm)	2,645 Ft/L lbs
Bead breaker movement	Automatic / Manual indent
Rotation motor	2Hp / 1,5 Kw in motor
Recommended air supply	115-145 PSI / 8-10 bar
Power supply	220v / 1Ø / 60 Hz

\* Depending on wheel offset

