

R247D.CL CENTER LOCKING HIGH VOLUME SWING ARM CHANGER

Center post design and productivity features make this the go-to pro performance swing arm tire changer for the busiest tire centers.

Easy to use center post mounting increases productivity and reduces the risk of wheel damage. Comes standard with metal and plastic mounting and demounting heads.

VARIABLE SPEED CONTROL INVERTER

Regulates rotational speed by slowing as the stress on the bead increases avoiding any damage to the tire. The double-acting bead breaker cylinder is designed to work on low-profile and large steel or alloy rims.

FEATURES

- Quick locking wheel centering system
- Integrated wheel lift
- Lower bead lifting roller
- Pneumatic top bead pressing tool
- Hand controlled side bead breaker
- 220v drive motor provides needed torque
- Storage cabinet
- Tire paste lubricant and brush
- Ships with NEMA L6-20P plug



**INTEGRATED
WHEEL LIFT**



**HAND
CONTROLLED
SIDE BEAD
BREAKER**

OPTIONAL ACCESSORIES

VSG1000A158

Universal flange for reverse, and Chrome Clad wheels

VSG1000A123

Plastic/Chrome Clad adapter for clamping wheels through locking holes

VSG1000A102

5 stud kit 110mm long for reverse rims. Used on VSG1000A87

VSG1000A11

Bead tire lever

VSG1000A152

Light truck adapter for centering locking tire changer - 19.5" wheels

VSG1000A18

Bead pushing roller

R247D.CL services:



Optional equipment may be required

TECHNICAL DATA	R247D.CL
Rim clamping	10"-30"
Maximum rim width	15"
Maximum tire diameter	47"
Max. bead breaker opening	15"
Bead breaker cylinder power at 145 psi	6,745 LBS
Rotation motor	2Hp / 1,5 Kw inverter
Recommended air supply	115-145 PSI / 8-10 bar
Power supply*	220v / 1Ø / 60 Hz VARIABLE SPEED



Lit# Rotary R247D.CL Changer Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.

Site Requirements:
220V / 1Ø / 20 amp power supply / 115-145 psi air supply



Eagle Automotive Equipment IV, Inc.

Turn key solutions for all your shop equipment needs.