

SPO16 CARGO TWO POST LIFTS

16,000 lbs. CAPACITY / SUPER DUTY SYMMETRIC LIFT

SERVICE LONGER VAN WHEELBASES WITH EASE

HEAVY DUTY 3-STAGE ARMS FEATURE A GREATER SPOTTING RANGE FOR SPECIFIC PICKUP POINTS



Minimum / Maximum Arm Reach: 36 13/16" to 74 13/16"
Standard with adjustable thread up adapters




AVAILABLE AS LOW CEILING MODELS
Overall Height: 3' 6" to 14' 6"
Ceiling Height Min: 13' 8" to 14' 8"


MODEL SHOWN: SPO16U0A0BL
SHOCKWAVE-EQUIPPED

INCLUDES:

- Thread up adapters for easy vehicle contact
- Set of four (4) clip-on rubber pads for adapters to spot unibody passenger cars
- Four (4) 5" adapter extensions and two (2) 10" adapter extensions for added lifting height and reach



FEATURES:

- 16,000 lbs. capacity
- 2 adjustable lift height options
- 3 column width options
- Rise height of over 75"
- 20 second lowering time
- Available with SHOCKWAVE™ power
- Original "Double S" column
- ALI Gold Certified

SUPERCHARGE SPO16 lifts with SHOCKWAVE™ SPEED

SHOCKWAVE DC powered lifts are the fastest in the world! Accelerate productivity and increase service numbers.



SCAN VIDEO CODE TO LEARN MORE

SPO16 CARGO MODELS

BL = Blue / RD = Red

HEAVY DUTY 3-STAGE ARMS Thread Up Adapters

STANDARD	SPO16N0A0BL SPO16N0A0RD
SHOCKWAVE EQUIPPED	SPO16U0A0BL SPO16U0A0RD
Rise*	77 13/32" - 78 13/32"
Overall Height	15' to 16' 6"
Overall Width	NARROW: 12' 11" STANDARD: 13' 5" WIDE: 13' 11"
Drive-thru	NARROW: 105 11/32" STANDARD: 111 11/32" WIDE: 117 11/32"
Inside Columns	NARROW: 120 15/32" STANDARD: 126 15/32" WIDE: 132 15/32"
Front & Rear Arm Min/Max Reach	36 13/16" - 74 13/16"
Min Adapter Height	5 13/32"
Min Adapter Height	3 3/8"
Min Bay Size	15' x 30'
Ceiling Height Min	15' 2" to 16' 8"
Motor / Voltage With SHOCKWAVE	2 HP, 208-230V 5 HP / 110V
Time of Rise / Descent With SHOCKWAVE**	81 / 20 seconds 60 / 19 seconds

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke
** Times vary depending on vehicle weight
Heights and widths reflect standard lift model settings

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com 



North / South America Information

Sales: 800.445.5438
insidesales@vsgdover.com

Tech. Support: 800.445.5438
technicalsupport@rotarylif.com

Global Contact Information

USA: 1.812.273.1622
Canada: 1.905.812.9920
Latin America / Caribbean: 1.812.273.1622
Brazil: +55.11.4534.1995

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/



Lit# Rotary SPO16 CARGO Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™. Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.