



SPO12 SERIES TWO POST LIFTS

12,000 lbs. CAPACITY / MEDIUM DUTY SYMMETRIC LIFT



Its size, wider drive-thru and larger footprint make the SPO12 the optimal 2 post lift for shops that work on taller, heavier vehicles.

Choose your:

- Lift height and width
- Power option
- Productivity accessories

SPO12-TA

Symmetric lift with TA truck adapters and 3-stage arms for greater vehicle reach.

SPO12-LC

LOW CEILING DESIGN

Shorter overhead height designed for shops with lower ceiling bays.

- 11' 8" overall height
- 11' 9" minimum required ceiling height

SPO12 WIDE

Wider stance provides an additional 17" of drive-thru width for larger trucks and vans.

Wide lift design provides the versatility for greater under vehicle access and less obstruction for service to battery electric vehicles.

LIFT SHOWN: SPO12-SW

Includes SHOCKWAVE™ DC power with onboard 110v charger providing 2X the lifting speed of conventional lifts.



SCAN THIS VIDEO CODE TO LEARN ABOUT THE BENEFITS OF ROTARY SHOCKWAVE LIFTS

SPO12 SERIES LIFTS FEATURE three-stage arms and polymer Truck Adapters primarily used on framed vehicles.

Adjustable adapters thread-up and come with stackable inserts and storage rack. No metal

- Three-stage arms for greater reach
- Original "Double S" column design
- Performance tested to 20,000 lift cycles
- Nationwide support
- ALI Gold Certified



Standard SPO12 and SPO12-SW lifts are available in 4 adjustable lift height options / models

ADD UP TO 3' OF ADDITIONAL HEIGHT FOR EURO-STYLE CARGO VANS



SYMMETRIC LIFT MODELS

BL = Blue / RD = Red

CONVENTIONAL 3-STAGE ARMS
Truck Adapters (TA)

CONVENTIONAL 3-STAGE ARMS
Truck Adapters (TA)

CONVENTIONAL 3-STAGE ARMS
Truck Adapters (TA)

STANDARD POWER		STANDARD MODEL SPO12N7T5BL SPO12N7T5RD	LOW CEILING MODEL SPO12N7TLBL SPO12N7TLRD	WIDE MODEL SPO12N7W6BL SPO12N7W6RD
SHOCKWAVE EQUIPPED		SPO12U7T5BL SPO12U7T5RD	N/A	N/A
Rise*	STANDARD SHOCKWAVE	75 3/4" - 78 1/8" 75 3/4" - 78 1/8"	75 3/4" - 78 1/8" N/A	75 3/4" - 78 1/8" N/A
Overall Height		13' 8"	11' 8"	13' 11-1/2"
Overall Width		11' 5-5/8"	11' 5-5/8"	12' 10-5/8"
Drive-thru		102 3/8"	102 3/8"	119 3/8"
Inside Columns		114 7/8"	114 7/8"	131 7/8"
Front / Rear Arm Reach	Minimum: 27 1/2" Maximum: 59"			
Rear Arm Min/Max	27 1/2" / 59"			
Min Adapter Height	4 3/4"			
Min Bay Size	12' x 26'	12' x 26'	14' x 26'	
Ceiling Height Min	13' 9"	11' 10-3/4"	14' 1/2"	
Motor / Voltage 1Ø	2 HP, 208-230V / 5 HP - 110V with SHOCKWAVE			
Time of Full Rise	60 seconds / 25 seconds with SHOCKWAVE			

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke.

** Actual rise and descent times vary depending on vehicle weight. Heights and widths reflect standard settings. SPO12 lift colors come standard with your choice of red or blue.

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com     

Lit# Rotary SPO12 HWR Cutsheet.2023.01

©2023 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

North / South America Information

Sales: 800.445.5438
insidesales@vsgdover.com

Tech. Support: 800.445.5438
technicalsupport@rotarylif.com

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

Global Contact Information

USA: 1.812.273.1622

Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622

Brazil: +55.11.4534.1995

