

R146RP SUPER SWINGARM PRO MAX

HIGH PERFORMANCE / EXTRA-HEIGHT SPEEDCHANGER

The hand controlled R146RP SUPER includes an air-driven PLUS91SA HELPER ARM.

This bead top pressing and tire lifting device for large and special tires features a lower bead lifting roller and pneumatic top bead pressing tool.

NOTE: PLUS91SA IS NOT INSTALLED PRIOR TO DELIVERY

FEATURES

- Hand controlled, double-acting bead breaker
- Extra large 46" frame
- 110v drive motor supplies needed torque
- Air tank located in column
- Gear box is supported by steel plates to avoid flex
- Removable pedal assembly for easy maintenance
- Valve tray
- Tire paste lubricant and brush

STANDARD R146R SUPER ACCESSORIES

BEAD PUSHING ROLLER VSG800A59

For PLASTIC mount / demount head



BEAD PUSHING ROLLER VSG800A18

For METAL mount / demount head



STORAGE TRAY VSG800A77

Column mounted



STANDARD R146R SERIES ACCESSORIES

PLASTIC TOOL HEAD VSG800A60

Tool head with support



VSG800A117 Tool protection kit for metal mount / demount head (2 x kit)

VSG800A6 Clamp Protectors / 24" - 26" (4 pcs)

VSG800A11 Bead breaker protection / Qty. of 1
VSG800A11K / Qty. of 5

OPTIONAL ACCESSORIES

VSG800A107 Fast Fit Motorcycle Adapters
+ 5" from outside

SMALL WHEEL ADAPTER VSG800A111KIT

Reduces clamping capacity to 8" for
ATVs and lawn equipment tires.
- requires VSG800A107 wheel clamps



Lit# Rotary R146 Series Changer Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.
ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.

SHOWN: PLUS91SA HELPER ARM



Demounting lower bead



WHEEL LIFT ATTACHMENT VSG800A69

Works with PLUS91SA helper arm to safely lift tire and wheel assemblies



SHOWN:
R146R

Site Requirements: 110V / 115-145 psi air supply

ADDITIONAL R146 SERIES SWINGARM MODELS

R146R Base Model / Electric Motor

R146RA Base Model / Air Motor

R146RP Base Model / Electric Motor with Helper Arm

R146RAP Base Model / Air Motor with Helper Arm

R146RAPS Base Model / Air Motor with Helper Arm
with additional super accessories package

R146R Series services:



Optional equipment may be required

TECHNICAL DATA	R146 Series
External clamping	10" - 26"
Maximum torque to chuck	885 Ft/Lbs (1200 Nm)
Internal clamping	12" - 28.5"
Max. tire diameter	45" (1143 mm)
Max. tire width	15" (380 mm)
Max. bead breaker opening	15" (380 mm)
Bead breaker cylinder power at 145 psi	6,745 Ft/Lbs (3060 kg)
Power supply	110v / 1Ø / 60 Hz



SCAN CODE FOR
PRODUCT VIDEO