



# XA14 DRIVE-ON ALIGNMENT-READY LIFT



### Versatile, alignment-ready scissor lift offers an impressive 193" maximum wheel base - service wheel bases from 85.5" up to 198"

The lift's front radius gauge area has an extended, lengthened recess where multiple runway plates can be configured for vehicles with longer wheelbases.

#### **ALIGNMENT-READY LIFT INCLUDES**

- Two (2) turning radius gauges with adjustable 2" and 4" spacers for multiple turntable positions
- Two (2) 7,000 lbs. capacity rolling jacks



**MODEL** 

SCISSOR LIFT

#### **SURFACE MOUNT** XA14N110 **RECESSED MOUNT** XA14N111 **Lift Capacity** 14.000 lbs. Rise\* 72 3/4" surface mount Width Overall 91" Width Between Platforms 40" Length Overall 277" with ramps Length of Runway 216" **Extended Runway Length** 200" / surface mount Runway Width 25 1/2" Maximum Wheelbase 198" 10 3/4" Lowered Height Motor / Voltage 5 PH / 230V / Single Phase Time of Full Rise 77 seconds at rated load Time of Descent 47 seconds at rated load 85 - 110 psi Air Supply 14' x 27' **Recommended Bay Size**

\*Rise measures floor to top of runway deck at full stroke. Lift colors are red and blue - control console is gray

#### **OPEN THROUGH LIFT DESIGN**

Open front and rear creates space-saving working clearance through the entire middle of lift with open access points for easy movement.

#### **VERSATILE WHEELBASE RANGE**

216" long runways, oversized slip plates and easily adjusted radius gauge pockets accommodate a range of wheelbases.

- 85 1/2" to 193" for FOUR WHEEL ALIGNMENT
- 195" MAX. TWO WHEEL ALIGNMENT
- 198" for GENERAL SERVICE
- 25-1/2" wide runways

#### **FEATURES:**

- · Air Actuated Rear Slip Plate Locks
- Recessed / Surface Mount Options
- Longer Ramps are standard on surface models
- Base plate leveling system for easy installation

**Optional Extended Ramp Kits** for low clearance vehicles are available

# **Rotary Lift**

2700 Lanier Drive / Madison, IN 47250, USA
















#### North / South America Information

Control Unit

slip lock switch.

with robust, simple buttons

and switches for long life. Includes single point rear

Sales: 800.445.5438 insidesales@vsgdover.com

72-3/4" VERTICAL RISE

minimizes required bay space.

Technicians have the height to get repair

work done. True up /down lift movement

Tech. Support: 800.445.5438 technicalsupport@rotarylift.com

Government Sales: 800.445.5438 X5655

### **Global Contact Information**

USA: 1.812.273.1622 Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622

Brazil: +55.11.4534.1995

For additional information: rotarylift.com/Government-Purchasing-Assistance/